

# PULPMATE 550

## SPECIFICATIONS:

Height: 1850mm

Width

Beak Open: 1785mm

Beak Closed: 1660mm

Length: 1900mm

Clamping Diameter: 130-950mm

Minimum Stump Height: 50mm (2")

Clamp Cylinder Bore: 3"

No. of Cylinders: 2

## SAW SPECIFICATIONS:

Cutting Capacity: 50-900mm (2" - 35")

Bar length: 43"

Chain Type: 3/4" Pitch

Saw Motor: Rexroth A2FM45

Chain Speed: 3000-3500 RPM

Saw Rotate Motor: M&S MSY400


Saw Bar Rotation: 204 degrees

Bar Lubrication: Automatic

## WEIGHT:

2950 kg approx.

Suited to minimum 25 tonne base ex-



## RECOMMENDED HYDRAULIC CONTROLS:

Purpose Built Rexroth Control Valve Bank or OEM stackable valves

Rotation: Electric (Joystick Button)

Beak: Electric (Joystick Button)

Saw: Hydraulic (Footpedal)

Float Head Rotation: Electric (Joystick Button)

Float Bucket Cylinder: Electric (Joystick Button)

Float Rotation & bucket cyl: Electric (Joystick Button)

## ROTATION SYSTEM:

Continuous in either direction

Heavy Duty Slew Ring

Two Rexroth MCR10 Motors

Heavy Duty Pinion Gears

Rotation Torque: ftlb

## HYDRAULIC REQUIREMENTS:

Pressure: 300 Bar (Minimum: 220 Bar)

Flow: 220 L/Min (Minimum: 180 L/Min)



3/217 Colchester Road KILSYTH VIC 3137

Ph: 03 9761 4155

Fax: 03 9761 4947

Email: [info@hardwoodforestproducts.com.au](mailto:info@hardwoodforestproducts.com.au)

Web: [www.hfpaust.com.au](http://www.hfpaust.com.au)